

Premium Silver Silk

WEIGHT
290 gsmROLLWIDTH
100 cmAPPLICATION
Commercial

TECHNICAL SPECIFICATIONS

PROPERTY	TEST METHOD	VALUE
Basis Weight		290 gsm
Caliper		0.450 mm
MD Tensile		6.5 kN/m
CD Tensile		5.8 kN/m
MD Wet Tensile		1.7 kN/m
MD Tear		1400 mN/16PL
CD Tear		1300 mN/16PL
Opacity		95.0%
Smoothness		30 SU
Internal Bond		400 J/m2
Wet Expansion		1.5%

FIRE CLASSIFICATION

PROPERTY	STANDARD	CLASSIFICATION
Fire Classification	EN 13501-1:2018	Bs1-d0

ADDITIONAL INFORMATION

PROPERTY	DETAILS
Bond Strength	Good internal bond strength
Dimensional Stability	Good dimensional stability
Color Stability	Good color stability
Printing Compatibility	Gravure and flexo printing
Fixing Method	Glued with fleece wallcovering paste
Application	Wallcovering - glued

PRODUCT DESCRIPTION

290 gsm silk texture nonwoven wallcovering base with fleece backing, featuring a luxurious silver silk finish. Good internal bond strength, dimensional stability, and excellent color stability. Suitable for gravure and flexo printing. Applied as wallcovering, glued to non-combustible substrate.