

TUSKARA

RUGS

Project Essential

WEIGHT
2768 gsm

ROLLWIDTH
400x300 / 350 cm round

APPLICATION
Commercial

TECHNICAL DETAILS

PROPERTY	STANDARD	SPECIFICATION
Manufacturing process	DIN ISO 2424	Tufted 1/10"
Frontside structure	DIN ISO 2424	Cut pile - Saxony
Color	DIN ISO 2424	Chromojet print
Pile Material		Polyamid PA 6 - Econyl
Primary backing	DIN ISO 2424	PP Woven
Secondary backing	DIN ISO 2424	Felt Back
Pile weight	DIN ISO 2424	approx. 1200 g/m2
Total weight	ISO 8543	approx. 2500 g/m2
Pile height	ISO 1766	approx. 6.0 mm
Total thickness	ISO 1765	approx. 9.5 mm
Number of knots	ISO 1763	approx. 213,000 /m2
Width	DIN 3018	approx. 400 cm

FUNCTIONAL PROPERTIES

PROPERTY	STANDARD	RATING
Wear classification	EN1307:2014+A3:2018	33
Comfort rating	EN1307:2014+A3:2018	LC 3

PHYSICAL PROPERTIES

PROPERTY	STANDARD	CLASSIFICATION
Fire rating	DIN EN 13501-1	Cfl-s1

FASTNESSES

PROPERTY	STANDARD	RATING
Colour fastness to light	EN ISO 105-B02:2013	7

SUSTAINABILITY

PROPERTY	STANDARD	DETAILS
Emissions	TUV ProfiCert Premium	NR. 707107640-1
EPD		in Progress

PRODUCT DESCRIPTION

Premium tufted cut pile carpet with Saxony finish for commercial applications. Chromojet printed on sustainable Econyl Polyamid PA 6 with felt backing. Wear classification 33 for heavy commercial use. TUV ProfiCert Premium certified for low emissions.