

TUSKARA

WALLCOVERINGS

Raw Vinyl

WEIGHT
350 gsm

ROLLWIDTH
100 cm

APPLICATION
Commercial

TECHNICAL SPECIFICATIONS

PROPERTY	TEST METHOD	VALUE
Total Weight	ISO 2286-2	350 +/- 20 gsm
Weight Non-woven		60 +/- 20 gsm
Weight Coating		290 +/- 20 gsm
Coating Type		Acrylic lacquer (inkjet)
Thickness		Depends on embossing
Roll Width		100 cm
Roll Length		Custom value

FIRE CLASSIFICATION

PROPERTY	STANDARD	CLASSIFICATION
Fire Resistance (EU)	EN 13501-1	Bs1-d0
Fire Resistance (US)	ASTM E84	ASTM84
Fire Resistance (DIN)	DIN 4102	B1

ADDITIONAL INFORMATION

PROPERTY	DETAILS
Printing Inks	Latex, Eco-solvent, Solvent, UV
Washability	Extra washable
Lightfastness	7/8 Int. Woolscale
Chemical Resistance	Soap, Detergents, Alcohol
Not Resistant To	Ketones, Esters, Aromatics
Adhesives	Heavy duty wallcovering adhesive
Safety / Ecological	Non-hazardous

PRODUCT DESCRIPTION

350 gsm nonwoven wallcovering with specially formulated acrylic lacquer coating with exclusive inkjet properties. Suitable for Latex, Eco-solvent, Solvent and UV-curable inks. Extra washable with excellent chemical resistance.