

TUSKARA

RUGS

Soft Home

WEIGHT
3085 gsm

ROLLWIDTH
400x300 / 350 cm round

APPLICATION
Residential

TECHNICAL DETAILS

PROPERTY	STANDARD	SPECIFICATION
Manufacturing process	DIN ISO 2424	Tufted 1/10"
Frontside structure	DIN ISO 2424	Cut pile – Saxony
Color	DIN ISO 2424	Chromojet print
Pile Material		Polyamid PA 6.6
Primary backing	DIN ISO 2424	PP Woven
Secondary backing	DIN ISO 2424	Felt Back
Pile weight	DIN ISO 2424	approx. 1400 g/m2
Total weight	ISO 8543	approx. 2715 g/m2
Pile height	ISO 1766	approx. 7.5 mm
Total thickness	ISO 1765	approx. 10.5 mm
Number of knots	ISO 1763	approx. 178,000 /m2
Width	DIN 3018	approx. 400 cm

FUNCTIONAL PROPERTIES

PROPERTY	STANDARD	RATING
Wear classification	EN1307:2014+A3:2018	in Progress
Comfort rating	EN1307:2014+A3:2018	LC 5
Castor chair resistance	EN 985: Prufung A	in Progress

PHYSICAL PROPERTIES

PROPERTY	STANDARD	CLASSIFICATION
Fire rating	DIN EN 13501-1	Cfl-s1*1

FASTNESSES

PROPERTY	STANDARD	RATING
Colour fastness to light	EN ISO 105-B02:2013	6-7
Colour fastness to water		5
Rubbering fastness dry/wet		5/5

SUSTAINABILITY

PROPERTY	STANDARD	DETAILS
Emissions	TUV ProfiCert Premium	in Progress
EPD		in Progress

PRODUCT DESCRIPTION